

# DEFY INTERIOR CLEAR WOOD FINISH

## PRODUCT DATA

### DEFY Interior Clear Wood Finish

MANUFACTURER: SaverSystems  
Richmond, IN 47374  
800-860-6327  
Fax 765-935-4999  
www.saversystems.com

## DESCRIPTION

**DEFY Interior Acrylic-Satin Wood Finish** is a durable, non-yellowing, acrylic-based protective log and wood finish formulated for interior use. It is fast drying, nonflammable, and has very little odor. DEFY Interior Acrylic-Satin Wood Finish beautifies and protects interior wood from common household chemicals, grease, water, scuffing and abrasion. Product helps prevent fine dust penetration and makes cleaning easier. It's unique formula and clarity makes it perfect for use over natural wood and woods that are stained with water-based and oil-based stains. When applying DEFY Interior Acrylic-Satin Wood Finish over light colored oil-based stains, a slight ambering may occur. Always spot test on an inconspicuous area and let dry to ensure desired results.

## USES

DEFY Interior Acrylic-Satin Wood Finish can be used for log home interior walls, furniture, trim, paneling, doors, cabinets and any other interior wood surface. To clean surfaces protected with DEFY Interior Acrylic-Satin Wood Finish, damp wipe with soap and water, window cleaner, or mild detergent.

## BENEFITS

- Protects Wood
- Smooth Natural Finish
- Easy to apply
- Dries crystal clear
- Easy clean-up
- Low maintenance

## DIRECTIONS FOR USE

**Surface Preparation:** Surfaces must be clean and dry. Remove all wax, dirt, dust and other contaminants. Over New or Bare Wood: Sand Slightly with fine sandpaper (not steel wool) and remove all sanding dust. Over Stain and Finishes: Clean surfaces thoroughly. Remove all traces of wax, dirt and old finishes in poor condition. Sand lightly with fine sandpaper and remove all sanding dust. Test DEFY Interior Acrylic-Satin Wood Finish in an inconspicuous area and let dry to ensure desired results. Do not apply over sanding sealer or material containing silicone or stearate. Open windows and doors for adequate air movement. Apply between 50°F and 90°F.

## APPLICATION

Do not thin or dilute. Do not shake, stir with electric drill mixer to ensure proper mixing of product and stir occasionally during application. DEFY Acrylic-Satin Wood Finish appears opaque in container, but dries crystal clear. Product may be applied with a sprayer or a high quality synthetic bristle brush. For best results, apply a very thin first coat in one direction with the wood grain. DO NOT OVER BRUSH. Allow to dry for at least two hours; then sanding with fine 220grit sandpaper, remove all dust and apply next coat. Allow two hours of drying time between each coat. (2-3 coats are recommended for best results) After final coat, surface will be ready for light handling in four hours.

**Dry Time:** one to two hours depending on film thickness, temperature and humidity.

**Coverage:** First coat 200-300 square feet per gallon depending on the wood texture and porosity. Each additional coat is 400-500 square feet per gallon.

**Clean-up:** Clean brushes immediately after use with soap and water.

## MAINTENANCE

Remove all substances, which might stain or hold moisture on coated surfaces as quickly as possible. To clean coated surfaces use damp wiping with soap and water, mild detergent or window cleaner.

## CAUTIONS

### Keep out of reach of children!

Avoid contact with eyes and skin. Do not take internally. Use with adequate ventilation. Product is low in toxicity, but vapors may cause headaches. Always use a respirator when applying with a sprayer. For additional information consult the Material Safety Data Sheet for this product, you may go to our website [www.saversystems.com](http://www.saversystems.com) to retrieve one as well.

## LIMITED WARRANTY

Our recommendations for use of this product are based upon tests believed to be reliable. Since field conditions vary widely, the user must determine the suitability of the product for the particular use and specific method(s) of application. Due to the fact that SaverSystems has no control over surface preparation and application methods, no guarantee as to results are offered, expressed or implied. SaverSystems' warrants this product to be free from defects. SaverSystems' liability shall be limited in all events to supplying enough product to re-treat the specific areas to which defective product has been applied. This warranty does not include the cost of labor for re-application of product. SaverSystems shall not have any other liability including direct, incidental, or consequential damages. Some states do not allow the exclusion of incidental or consequential damages, so this limitation or exclusion may not apply to you. This warranty gives you specific legal rights. You may also have other rights that can vary from state to state.

## PACKAGING

Available in 1 and 5 gallon recyclable plastic containers.

## TRANSPORT AND STORAGE

DEFY UV-Resistant Clear Wood Finish is not considered hazardous under Department of Transportation regulations. Do not stack pallets. Keep product from freezing.

## PHYSICAL PROPERTIES

Color .....	Opaque
Composition .....	Acrylic resin blend
Solvent .....	Water
Solids by Weight .....	Approx.- .35%
Density .....	(8.5 #/gallon)
Flashpoint .....	None
Shelf Life .....	12-18 months
VOC Content (EPA 24).....	less than 200 gr/ltr