Material Safety Data Sheet

Code: LiquidWood A Page: 2

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: LiquidWood A

Date Prepared: 11/02/2009
Product Code: LiquidWood A

Type: Liquid Epoxide Resin

Class: Epoxide

SECTION 2: HAZARDOUS INGREDIENTS

Trade Secret: Proprietary Liquid Prepolymers

SECTION 3: PHYSICAL DATA

Boiling Point: >400° FSol. In Water: NegligibleVapor Press: NASp. Gravity: 1.12-1.15Vapor Density (Air=1): NA% Volatile by Vol.: <0.1</td>

Appearance and Odor: Clear, colorless liquid, mild, aromatic odor.

SECTION 4: FIRE AND EXPLOSION HAZARD DATA

Flash Point: >200° F

Method Used: ASTMD92-96, TOC

Flammable Limits (STP in Air)

LFL: Not deter

UFL: Not deter

Extinguishing Media: Foam, CO₂, dry chemical. Special Fire Fighting Equipment and Hazards: None.

SECTION 5: HEALTH HAZARD DATA

Occupational Exposure Limits:

OSHA PEL/TWA: Not established PEL/STEL: Not established

ACGIH TLV/TWA: Not established

Ingestion: Low Single Oral Toxicity: LD50 (Rat): >2000 mg/kg. Eye Contact: Minor transient irritation. No corneal injury likely. Skin Contact: Only minor irritation. May be a skin sensitizer. Skin Absorption: Not likely to be absorbed in toxic amounts.

Inhalation: Not likely a problem at room temperature. Vapors from heated material may be

irritating.

Effect of Overexposure: None known.

First Aid Procedures:

Eyes: Irrigate with flowing water immediately for 5 minutes. Refer to medical personnel. **Skin:** Contact will probably cause no more than irritation. Flush skin with water or soap and

water. Wash clothing before reuse.

Inhalation: Remove to fresh air if effects occur. Consult medical personnel. **Ingestion:** Low in toxicity. Induce vomiting if large amounts are ingested.

Note to Physician:

Eyes: Injury is unlikely. Stain for evidence of corneal injury. Consult ophthalmologist.

Skin: May cause moderate irritation. Treat as any contact dermatitis. Known or suspected weak

sensitizer. Not likely to be absorbed in acutely toxic amounts.

Respiratory: Injury is unlikely.

Oral: Low in toxicity.

Systemic: Human effects not established. No specific antidote. Treatment should be based on

the sound judgment of the physician and the individual reaction of the patient.

SECTION 6: REACTIVITY DATA

Stability: Stable under normal conditions. Prolonged excessive heat may cause partial

degradation.

Incompatibility: Active acids and bases.

Hazardous Decomposition Products: None under normal conditions.

Hazardous Polymerization: Will not occur by itself, but masses of more than 3-5 pounds of product plus an aliphatic amine may cause irreversible reaction with considerable heat buildup.

SECTION 7: SPILL, LEAK AND DISPOSAL PROCEDURES

Action to Take For Spills: (Use appropriate safety equipment.) Soak in absorbent material or scrape up. Residual resin can be removed by use of non-flammable solvent such as methylene

chloride.

Disposal Method: Do not dump into any sewers, on the ground or into any body of water. All disposal methods must be compliant with all federal, state and local laws and regulations.

SECTION 8: SPECIAL HANDLING INFORMATION

Ventilation: Sufficient to minimize vapor exposure if generated.

Respiratory Protection: None likely needed.

Protective Clothing: Clean, body-covering clothing. Disposable plastic or rubber gloves.

Disposable containers and paper in work area.

Eye Protection: Safety glasses.

SECTION 9: SPECIAL PRECAUTIONS IN HANDLING AND STORAGE AND ADDITIONAL INFORMATION

Precautions to Be Taken In Handling and Storage: None except normal handling care. Practice good caution and personal cleanliness to avoid eye and skin contact. Avoid breathing vapors if generated.

SECTION 10: TRANSPORTATION REQUIREMENTS

Proper Shipping Name:
Hazardous Class:
ID Number:
Packing Group:
Not Regulated
Not Regulated
Not Regulated

THE INFORMATION HEREIN IS GIVEN IN GOOD FAITH, BUT NO WARRANTY, EXPRESS OR IMPLIED IS MADE.

Material Safety Data Sheet

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: LiquidWood B Date Prepared: 11/02/2009

Product Code: LiquidWood B Type: Curing Agent

Class: Formulated liquid amines

SECTION 2: HAZARDOUS INGREDIENTS

Trade Secret: Proprietary Liquid Amines

SECTION 3: PHYSICAL DATA

Boiling Point: >250° F Sol. In Water: Moderate Vapor Press: NA **Sp. Gravity:** 0.92-0.96 Vapor Density (Air=1): NA % Volatile by Vol.: <5

Appearance and Odor: Clear, amber-colored liquid. Light ammonia odor.

SECTION 4: FIRE AND EXPLOSION HAZARD DATA

Flash Point: >200° F Flammable Limits (STP in Air) LFL: Not deter. UFL: Not deter. Method Used: ASTM D92-96

Extinguishing Media: Foam, CO₂, dry chemical. Special Fire Fighting Equipment and Hazards: None.

SECTION 5: HEALTH HAZARD DATA

Occupational Exposure Limits:

OSHA PEL/TWA: Not established PEL/STEL: Not established

ACGIH TLV/TWA: Not established

Ingestion: LD50 > 16 g/kg. Eye Contact: Extreme irritation.

Skin Contact: Only minor irritation. Primary irritation test score 1.2. **Skin Absorption:** Prolonged or repeated contact may cause injury.

Inhalation: Not likely a problem at room temperature. Vapors from heated material may be

Effect Of Overexposure: May cause skin sensitization. None other known.

First Aid Procedures:

Eyes: Irrigate with flowing water immediately for at least 10 minutes. Refer to medical

personnel.

Skin: Wipe off excess. Scrub with soap and water followed by water rinse. Wash clothing

Inhalation: Remove to fresh air if effects occur. Consult medical personnel. Ingestion: Low in toxicity. Induce vomiting if large amounts are ingested.

Note to Physician:

Eyes: Extremely irritating. Stain for evidence of corneal injury. Consult ophthalmologist. Skin: Acute dermal toxicity. Treat as contact dermatitis. Known or suspected sensitizer. Not

Code: LiquidWood B

Page: 2

likely to be absorbed in acutely toxic amounts. Respiratory: Injury is unlikely.

Systemic: Human effects not established. No specific antidote. Treatment should be based

on the sound judgment of the physician and the individual reaction of the patient.

SECTION 6: REACTIVITY DATA

Stability: Stable under normal conditions. Prolonged excessive heat may cause partial

degradation.

Incompatibility: Epoxy resins under uncontrolled conditions.

Hazardous Decomposition Products: None under normal conditions.

Hazardous Polymerization: None.

SECTION 7: SPILL, LEAK AND DISPOSAL PROCEDURES

Action to Take For Spills: (Use appropriate safety equipment.) Soak in absorbent material or

scrape up. Scrub with 5% acetic acid to emulsify. Rinse with very hot water.

Disposal Method: Do not dump into any sewers, on the ground or into any body of water. All

disposal methods must be compliant with all federal, state and local law and regulations.

SECTION 8: SPECIAL HANDLING INFORMATION

Ventilation: Sufficient to minimize vapor exposure if generated.

Respiratory Protection: None likely needed.

Protective Clothing: Clean, body-covering clothing. Disposable plastic or rubber gloves.

Disposable containers and paper in work area.

Eye Protection: Safety glasses.

SECTION 9: SPECIAL PRECAUTIONS IN HANDLING AND STORAGE AND ADDITIONAL

INFORMATION

Precautions to Be Taken In Handling and Storage: None except normal handling care. Practice good caution and personal cleanliness to avoid eye and skin contact. Avoid breathing

vapors if generated.

SECTION 10: TRANSPORTATION REQUIREMENTS

Not Regulated Proper Shipping Name: **Hazardous Class:** Not Regulated ID Number: Not Regulated

Packing Group

THE INFORMATION HEREIN IS GIVEN IN GOOD FAITH, BUT NO WARRANTY, EXPRESS OR IMPLIED IS MADE.