
Material Safety Data Sheet

PRODUCT NAME: SYMPHONY
PRODUCT COLORS: Clear Satin

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: Sashco, Inc.
ADDRESS: 10300 E. 107th Place, Brighton, CO 80601
EMERGENCY PHONE: 1-800-535-5053
INFORMATION PHONE: 1-800-767-5656
DATE REVISED: August 3, 2009
NAME OF PREPARED BY: Andrew Spoelstra
REASON REVISED: Annual Review
CODE IDENTIFICATION: N/A
PRODUCT IDENTIFICATION: Water-based Clear Coating

| Health | HMIS Ratings | | PPE |
|--------|--------------|------------|-----|
| | Flammability | Reactivity | |
| 1 | 0 | 0 | B |

===== SECTION II – HAZARDOUS INGREDIENTS =====

Dipropylene glycol monomethyl ether CAS #034590-94-8 <3%
Dipropylene glycol butyl ether CAS #29911-28-2 <3%

===== SECTION III – PHYSICAL DATA =====

SPECIFIC GRAVITY (H₂O=1): 1.02
PERCENT VOLITILE BY WEIGHT (%): 75%
EVAPORATION RATE (WATER=1): <1
SOLUBILITY IN WATER (cured film): Insoluble
APPEARANCE AND ODOR: Semi-opaque liquid, mild amine odor
BOILING POINT (°F) 212°F
VAPOR PRESSURE (mm Hg): N/D
VAPOR DENSITY (AIR=1): >1

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (°F): 200°F
FLAMMABLE LIMITS: No data available
EXTINGUISHING MEDIA: Water fog, CO₂, dry chemical, foam.
SPECIAL FIRE FIGHTING PROCEDURES: Normal fire fighting procedures may be used.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Container may burn and leak in heat of fire.

===== SECTION V - HEALTH HAZARD DATA =====

THRESHOLD LIMIT VALUE: N/D
EFFECTS OF OVEREXPOSURE: No data available.
EMERGENCY AND FIRST AID PROCEDURES:
EYES: Immediately flush with large quantities of water for at least 15 minutes. If irritation persists, see a medical doctor.
SKIN: Wash with soap and water and rinse thoroughly. Wash contaminated clothing before use.
INHALATION: Remove to fresh air.

INGESTION: If large quantities are swallowed, DO NOT INDUCE VOMITING – seek medical help.

===== SECTION VI - REACTIVITY DATA =====

STABILITY: Stable
INCOMPATIBILITY: Strong oxidizing agents
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, oxides of nitrogen.
HAZARDOUS POLYMERIZATION: Will not occur

===== SECTION VII - SPILL OR LEAK PROCEDURES =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Do not let spilled or leaking material to enter watercourse. May be toxic to aquatic life. Absorb with inert material. Sweep or scrape up and containerize. Rinse affected area thoroughly with water.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and Local regulations.

===== SECTION VIII - SPECIAL PROTECTION INFORMATION =====

RESPIRATORY PROTECTION: Approved type recommended when product is being sprayed.
VENTILATION: Mechanical ventilation may be required in enclosed areas.
PROTECTIVE GLOVES: Impervious gloves if frequent or prolonged contact could occur.
EYE PROTECTION: Recommended.
OTHER PROTECTIVE EQUIPMENT: N/A

===== SECTION IX - SPECIAL PRECAUTIONS =====

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep from freezing.

OTHER PRECAUTIONS: Wash thoroughly after handling. Keep out of reach of children.

===== SECTION X - DISCLAIMER =====

DISCLAIMER:
The information contained herein is based on data available at the time of preparation of this data sheet and which Sashco Inc. believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. Sashco, Inc. shall not be responsible for the use of this information or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment and the health and safety of your employees and users of this material.

N/A = not applicable N/D = not determined