



# LogHog<sup>®</sup>

**FASTER EASIER STRONGER**

**LogHog is an extra heavy-duty log home fastener, engineered for specific log home construction applications. Its oversized head, thicker diameter and additional thread, offers increased draw-down and holding power.**

- No predrilling
- Self countersinking headstyle
- Increased draw down power for warped logs
- Increased holding power
- Removable
- Corrosion resistant
- No sledge hammer damage
- Greatly reduced labor time
- 100% American Made

Photograph should not be used as a reference for fastening patterns.



**For more information or free samples,  
call FastenMaster at 800-518-3569.**

## INSTALLATION PROCEDURE

- Use a 1/2", high torque, low RPM drill.
- Install LogHog perpendicular to the log.
- Countersink the LogHog a minimum of 1/4".

### FEATURES:

- Oversized washer head and increased thread combine for dramatically increased pull-down for warped and twisted logs.
- Installs much faster and easier than lags & spikes
  - Saves time and fatigue
  - Dramatically lowers installed cost
- Requires no predrilling
  - Eliminates on-site predrilling
  - Eliminates manufacturing drill stations
- Countersinks into log
  - Allows log to settle naturally
- Removable and reusable
- Eliminates jarring and damage caused by a sledge hammer
- Engineered for increased strength and performance

For complete engineering data, please see our official ICC ESR-1078 report at: [www.icc-es.org/reports/pdf\\_files/ICC-ES/1078.pdf](http://www.icc-es.org/reports/pdf_files/ICC-ES/1078.pdf)

PHYSICAL DATA	Item #	Length	Thread Length	Quantity per Pack*	Weight
Thread Diameter: .320	LHOG007	7"	3"	250	22 lb
Shank Diameter: .229	LHOG009	9"	3"	250	28 lb
Head Style: Hex Head	LHOG010	10"	3"	250	31 lb
*Indicates quantity per box. One special hex head driver bit and heavy duty washers in each box.	LHOG011	11"	3"	250	34 lb
	LHOG012	12"	3"	250	37 lb
	LHOG013	13"	3"	250	40 lb
	LHOG015	15"	3"	150	28 lb

## PRODUCT FEATURES

5/16" HEX HEAD  
 (1 FREE DRIVER BIT IN EACH BOX)

WIDE WASHER HEAD FOR  
 INCREASED PULL-DOWN

PATENTED HEAD STYLE  
 COUNTERSINKS ITSELF  
 DURING INSTALLATION

15/64" SHANK DIAMETER

MADE OF HEAT-TREATED STEEL  
 FOR DRAMATICALLY INCREASED  
 STRENGTH AND DRIVABILITY

ULTRA--COATED FOR UNMATCHED  
 CORROSION RESISTANCE

3" OF THREAD WITH  
 5/16" MAJOR DIAMETER

GIMLET POINT FOR  
 FAST DRILLING

