



- A safe, effective cleaner designed to remove mold, mildew and dirt from wood surfaces.
- Makes most wood surfaces "stain ready."
- Helps remove "graying" caused by ultraviolet light.
- Removes mill glaze from smooth wood surfaces.
- Contains NO chlorine bleach.
- Will not harm shrubs or landscaping.

DIRECTIONS FOR USE

- Mix 4 cups of Wood ReNew with 5 gallons of water and stir (if less than 5 gallons is required, mix 12 tablespoons of powder per gallon). Wait 10 minutes to allow the solution to thicken. Mix only enough solution to use in five hours.
- Apply solution liberally to the surface with a mop, broom or brush. Clean from the bottom up, rinse from the top down.
- Allow solution to remain on the wood for 10 minutes. If it begins to dry out, mist with a water hose.
- If necessary, use a broom or stiff brush to help clean the surface.
- Rinse thoroughly with a pressure washer. We strongly recommend the use of pH Strips to verify adequate rinsing. Heavily stained or discolored areas may need a second application. Rinse plants shrubs and grass after use.
- On some types of wood the cleaned surface may become blotchy or dark. Use OXcon Blonding Agent to lighten the color of the wood and even out the wall.

CAUTION: Keep out of reach of children. Powder is an eye irritant.

Eye Contact: Immediately flush eyes with large amounts of water for 15 minutes. Seek medical aid.

Skin Contact: Remove from skin and wash thoroughly. Remove contaminated clothing.

If Swallowed: Drink large amounts of water. Do not induce vomiting. Seek medical aid if irritation develops.

PERMA-CHINK™ SYSTEMS, INC. Eastern Division Western Division Colorado Montana Minnesota Sevierville, TN
1-800-548-3554 1-800-548-1231 1-800-433-8781 1-800-479-7090 1-877-244-6548 1-865-774-3307

www.permachink.com **NET WEIGHT: 9.3 lbs. / 4.22 kg.** Rev 6/07